

24W Gigabit PoE Injector G0720



Features

Output Voltage: 48V0.5A

Power:Max.24W

G0720 PoE Injector Technical Data

PoE Standard	No Detection – passive injector	
Input Power:	100-240VAC;50-60Hz 0.75A	
Power over Ethernet Output	Output: 48V0.5A	
Power Consumption:	24W max	
RJ-45 pin assignment and polarity	Power: Pins 4/5(+), 7/8(-)	
Data Rate:	10/100/1000Mbps	
MTBF:	500K Hours	
Safety Approval:	UL/cUL,GS,CB,FCC,CE	
Efficiency	VI	
Standards:	IEEE 802.3 10Base-T	IEEE 802.3U 100Base-TX
	IEEE 802.3ab 1000Base-T	IEEE 802.3af Power over Ethernet
	IEEE 802.3at Power over Ethernet Plus	
LED Indicator	AC power; PoE Active	
Interface:	1 "Data ' In RJ-45 Ethernet Port 1 "Data+Power" Output RJ-45 Ethernet Port 1 AC Input Power socket	

Environmental

Operating Temp:	0°C to +40°C
Storage Temp:	-40°C to +70°C
Humidity:	0 to +95%CRH

Mechanical

Weight:	133g	
Dimension(L*W*H):	97*53.5*33.5mm	114*53.5*67.5mm(ear)

Package:

CTN: 44.5*43.5*28cm/60pcs per ctn
N.W: 15.6KGS G.W: 17.26KGS

Application:

Voip/CCTV Camera/Wireless AP/RFID readers/Bluetooth AP/IP print servers/Security systems